

Domain Analysis of IL-1 Receptor-Associated Kinase 1

Sim-Hui Tee

Multimedia University, Persiaran Multimedia 63100 Cyberjaya, Selangor, Malaysia

shtee@mmu.edu.my

Abstract

There are four IL-1 Receptor-Associated Kinase (IRAK) family members in mammals, one of which is IRAK1. IRAK1 interacts with IRAK4, which is associated with MyD88 adaptor protein upon ligand stimulation. This research aims to study the domains of IRAK1, understanding of which is important to yield insights into the functional role of IRAK1 in the pathogen sensing mechanism. The results obtained from this study may guide further research in the immunotherapy studies on the Toll-Like Receptor (TLR) signaling pathway.

Keywords

Bioinformatics; Gene; Protein; IRAK1; Domain Analysis; Kinase

Introduction

IL-1 Receptor-Associated Kinase 1 (IRAK1) is an important kinase that is implicated in the pathogen sensing signaling pathways in the immune system. IRAK1 has been reported (Takeshita and Ishii 2008) to act as a triggered kinase in the detection of CpG DNA by Toll-like receptor 9 (TLR9). Besides, it was found that IRAK1 plays a significant role as a signal amplifier that would culminate in the activation of NF- κ B (O'Neill 2006). Although IRAK1 was not found to involve in the inflammasome signaling pathway, IRAK4, a member from the same kinase family as IRAK1, was reported to assemble with MyD88 in the NLRP3 inflammasome activation (de Nardo and Latz 2011).

In the TLR signaling pathway, MyD88 adaptor protein is associated with TLRs via Toll-IL-1 receptor (TIR) domain interactions. The bound TLR-MyD88 complex then recruits IRAK4 by binding to its death domain. The activated IRAK4 further phosphorylates IRAK1, leading to the activation of downstream Traf-6, Tak-1, inhibitor of NF- κ B (IKK), IRF7, and transcription factor NF- κ B (O'Neill 2006; Blasius and Beutler 2010). Activated NF- κ B will translocate into nucleus and regulate the expression of type I interferon production. The appropriate level of type I interferon is critical not

only in the immune defense against pathogens (Axtell and Steinman 2008); its aberration will have enormous impacts on the autoimmunity (Ewald and Barton 2011).

Structural insight of the proteins is important for the disclosure of the function. Besides, structural studies also provide clues on the interaction between ligands and their receptors (Wei et al. 2011). In the field of protein science, structural studies normally are carried out by electron microscopy (Nasertorabi et al. 2011), NMR techniques (Wang et al. 2011), and crystallography (Piotrowski et al. 2009). These approaches are complementary in the efforts to better understand the protein structure and function (Hunter et al. 2011). Despite the widespread use of physical approaches, computational approach has also been used increasingly due to its efficiency in the biological research. To date, computational analysis of the biological processes and entities has been applied in various fields, such as cellular pathways (Zhang et al. 2009), cytoskeleton studies (Dodson and Dimitrakopoulos 2010), protein structure (Kim 2004; Arakaki et al. 2004; Hinsen 2008), RNA (Levenkova et al. 2004; Jonikas et al. 2009; Muller 2005), viral studies (Zhou et al. 2005; Itakura et al. 2010), immunogenetics (Massari et al. 2012), signalling pathways (Xu and Wong 2008; Fijarewicz et al. 2007; Lai et al. 2009), cellular energies (Andronescu et al. 2010), oncology (Han 2010; Wang et al. 2007; Oh and Gao 2011; Wang et al. 2011), molecular docking (Axenopoulos et al. 2011; Zhang et al. 2005; Hussain et al. 2010; Teixeira et al. 2011), protein folding (He et al. 2009; Roche et al. 2011; Csaba and Zimmer 2010), carbohydrate structure (Ranzinger et al. 2011), and drug discovery (Sato et al. 2012; Kushwaha and Shakya 2010).

In this research, a computational approach has been adopted to analyze the domains of IRAK1 protein. Both active site and substrate binding site of IRAK1 were studied in detail. The best template for IRAK1 was predicted in this study. The insights of this research may guide further research in the

immunotherapy studies of IRAK1-implicated pathways.

Methods

The nucleotide and amino acid sequence of IRAK1 were retrieved from National Center for Biotechnology Information (NCBI). We used PSI-BLAST (Altschul et al. 1997) for distant homology recognition. Cn3D version 4.3 was used to simulate the domains of the protein. FFAS03 method (Jaroszewski et al. 2005) has been used for the calculation of the confidence score for the structural domains of IRAK1. Sequence alignment between

target protein and template protein was carried out using SCWRL (Krivov et al. 2009) and JACKAL modelling approach. Lastly, Pcons server (Lundstrom et al. 2001) was used to validate the structure of IRAK1.

Results and Discussion

Sequence alignment was performed on the active site and substrate binding site of IRAK1. Fig. 1 illustrates the alignment for active site, with the domain highlighted in yellow. All of the proteins shown in Fig. 1 are kinases. Fig.2 illustrates the alignment for substrate binding site.




FIG. 1 SEQUENCE ALIGNMENT OF THE ACTIVE SITE




FIG. 2 SEQUENCE ALIGNMENT OF THE SUBSTRATE BINDING SITE.

The abbreviation of the molecules presented in Fig. 1 and Fig. 2 is as such: 1F3M_C is Chain C, Crystal Structure of Human Serine/Threonine Kinase PAK1; 1L3R_E is hain E, Crystal Structure of A Transition State Mimic of The Catalytic Subunit of Camp-Dependent Protein Kinase; 1FGI_A is Chain A, Crystal Structure of The Tyrosine Kinase Domain of Fibroblast Growth Factor Receptor 1 In Complex With Su5402 Inhibitor; 1T4H_B is Chain B, Crystal Structure of The Kinase Domain of Wnk1; gi 68125618 is protein kinase (*Leishmania* major strain Friedlin); gi 48428484 is Serine/threonine-protein kinase PINK1; gi 78045619 is protein kinase (*Xanthomonas campestris* pv. *vesicatoria* str. 85-10); gi 50057639 is Protein kinase, (*Paramecium tetraurelia*); gi 125291 is Serine/threonine-protein kinase HAL4/SAT4.

From the sequence alignments, it was found that the extent of sequence identity is low, hence it is quite unlikely to identify a meaningful putative functional relationship, which is one of the objectives of the sequence alignment (Batzoglou 2005). The simulated domains are given in Fig. 3 (Ball and Stick model) and Fig. 4 (worms model), respectively. Homology relationship can be accurately recorded by the structural similarity, due to the fact that structural similarity is preserved beyond sequence similarity. Understanding of the three-dimensional structure of a protein may facilitate the understanding of the function of each domain (Vogel et al. 2004).




FIG. 3 PROTEIN DOMAINS (BALL AND STICK MODEL)




FIG. 4 PROTEIN DOMAINS (WORMS MODEL)

FFAS03 method (Jaroszewski et al. 2005) has been used for the calculation of the confidence score for the structural domains of IRAK1. Table 1 lists the top 10 best matched templates with IRAK1. It is apparent that 2nru protein is the most probable protein template that matches the structure of IRAK1.

TABLE 1 BEST MATCHED PROTEIN TEMPLATES FOR IRAK1 (USING FFAS03)

Confidence Score	Targets	Protein length (aa)	Description
-40.40	2nru	307	Interleukin-1 receptor-associated kinase 4
-40.00	3hgm	327	Protein kinase
-37.70	3t18	349	BRASSINOSTEROID INSENSITIVE 1-associated rece
-30.80	2qlu	314	Activin receptor type IIB
-30.80	3q4t	322	Activin receptor type-2A
-30.40	3p86	309	Serine/threonine-protein Kinase CTR1
-30.10	4f0f	287	Serine/threonine-protein Kinase roco4
-29.80	3g2f	336	Bone morphogenetic Protein receptor type-2
-29.10	3dtc	271	MAPK
-28.00	3s95	310	LIM domain kinase 1

Based on the confidence score listed in Table 1, we identified 2nru as the potential protein template to model the structure of IRAK1. When there is a clear sequence relationship between a target protein and a

known structure, structural templates can be used to yield an accurate core model (Moult 2005). We modelled IRAK1 against 2nru to find the identical residues. Such approach has been used in the experiment to study the glycosylase domain of DML proteins (Ponferrada-Marín et al. 2011). In this study, IRAK1 was aligned with 2nru (aa: 15) starting at amino acid position 208. Fig. 5 demonstrates the identical residues of both strands, as highlighted in red.



FIG. 5 PROTEIN STRUCTURE MODELLING

To validate our results, we used Pcons server to predict the structure of IRAK1. Table 2 lists the predicted matches.

TABLE 2 BEST MATCHED PROTEIN TEMPLATES FOR IRAK1 (USING PCONS)

Rank	Score	Targets
1	3e-98	2nru
2	3e-90	1vjy
3	4e-89	2b7a
4	4e-87	2fb8
5	4e-86	2eva
6	4e-86	1yvj
7	1e-80	1sm2
8	9e-78	2dq7
9	2e-77	1k2p

Comparing Table 2 with Table 1, 2nru is the best template yielded using FFAS03. Besides, it is also validated by Pcons server. It has four chains (A, B, C, D) with a structure weight of 140266.73. The crystal structure of this protein in the phosphorylated form has been reported by Wang et al. 2006. Further evidence from the bound protein assembly suggests that both IRAK1 and 2nru are assembled with MyD88 in the similar way (Honda et al. 2004). Thus, 2nru represents the best matched protein template for IRAK1.

Conclusion

IRAK1 is one of the important kinases in the pathogen sensing pathway. It is found to bind to the MyD88 adaptor protein in the signaling cascade, which is leading to the activation of NF-κB transcription factor. The domain study of IRAK1 is important for the disclosure of its functional role in the cytokine production and subsequent recruitment of lymphocytes to the sites of inflammation. In this study, we found that the structure of IRAK1 is closely resembled to 2nru, which suggests that IRAK1 and IRAK4 are highly homologous. Because both IRAK1 and IRAK4 have domain similarity to MyD88, it is of interest to study other potential MyD88-bound proteins which are yet to discover. The domain analysis of IRAK1 may provide insights into the therapeutic strategies that target MyD88 signaling pathway.

REFERENCES

Altschul, S.F., Madden, T.L., Schaffer, A.A., Zhang, L., Zhang, Z., Miller, W., and Lipman, D.J. “Gapped BLAST and PSI-BLAST: A New Generation of Protein Database Search Programs.” *Nucleic Acids Research* 25 (1997): 3389-402.

Andronescu, Mirela., Condon, Anne., Hoos, Holger H., Mathews, David H., and Murphy, Kevin P. “Computational Approaches for RNA Energy Parameter Estimation.” *RNA* 16 (2010): 2304-18.

Arakaki, Adrian K., Zhang, Yang., and Skolnick, Jeffrey. “Large-scale Assessment of the Utility of Low-resolution Protein Structures for Biochemical Function Assignment.” *Bioinformatics* 20 (2004): 1087-96.

Axenopoulos, Apostolos., Daras, Petros., Papadopoulos, Georgios., and Houstis, Elias N. “A Shape Descriptor for Fast Complementarity Matching in Molecular Docking.” *IEEE/ACM Transactions on Computational Biology and Bioinformatics* 8 (2011): 1441-57.

Batzoglou, Serafim. “The Many Faces of Sequence Alignment.” *Briefings in Bioinformatics* 6 (2005): 6-22.

Blasius, Amanda, and Beutler, Bruce. “Intracellular Toll-like Receptors.” *Immunity* 32 (2010): 305-15.

Csaba, Gergely., and Zimmer, Ralf. “Vorescore—Fold Recognition Improved By Rescoring of Protein Structure Models.” *Bioinformatics* 26 (2010): 1474-81.

De Nardo, Dominic, and Latz, Eicke. “NLRP3 Inflammasomes Link Inflammation and Metabolic Disease.” *Trends in Immunology* 32 (2011): 373-79.

- Dodson, W.R., and Dimitrakopoulos, P. "Tank-treading of Erythrocytes in Strong Shear Flows via a Nonstiff Cytoskeleton-based Continuum Computational Modeling." *Biophysical Journal* 99 (2010): 2906-16.
- Ewald, Sarah, and Barton, Gregory. "Nucleic Acid Sensing Toll-like Receptors in Autoimmunity." *Current Opinion in Immunology* 23 (2011): 3-9.
- Fujarewicz, Krzysztof., Kimmel, Marek., Lipniacki, Tomasz., and Świerniak, Andrzej. "Adjoint Systems for Models of Cell Signaling Pathways and Their Application to Parameter Fitting." *IEEE/ACM Transactions on Computational Biology and Bioinformatics* 4 (2007): 322-35.
- Han, Xiaoxu. "Nonnegative Principal Component Analysis for Cancer Molecular Pattern Discovery." *IEEE/ACM Transactions on Computational Biology and Bioinformatics* 7 (2010): 537-49.
- He, Yi., Zhou, Rui., Huang, Yanzhao., and Xiao, Yi. "Foldable Subunits of Helix Protein." *Computational Biology and Chemistry* 33 (2009): 325-28.
- Hinsen, Konrad. "Structural Flexibility in Proteins: Impact of the Crystal Environment." *Bioinformatics* 24 (2008): 521-28.
- Honda, K., Yanai, K., Mizutani, T., Negishi, H., Shimada, N., Suzuki, N., Ohba, Y., Takaoka, A., Yeh, W.C., and Taniguchi. "Role of A Transductional-Transcriptional Processor Complex Involving MyD88 and IRF-7 in Toll-Like Receptor Signalling." *Proceedings of the National Academy of Sciences of the United States of America* 101 (2004): 15416-15421.
- Hunter, M.S., DePonte, D.P., Shapiro, D.A., Kirian, R.A., Wang, X., Starodub, D., Marchesini, S., Weierstall, U., Doak, R.B., Spence, J.C.H., and Fromme, P. "X-ray Diffraction from Membrane Protein Nanocrystals." *Biophysical Journal* 100 (2011): 198-206.
- Hussain, Abrar., Melville, James L., and Hirst, Jonathan D. "Molecular Docking and QSAR of Aplyronine A and Analogues: Potent Inhibitors of Actin." *Journal of Computer-Aided Molecular Design* 24 (2010): 1-15.
- Itakura, Jun., Kurosaki, Masayuki., Itakura, Yoshie., Maekawa, Sinya., Asahina, Yasuhiro., Izumi, Namiki., and Enomoto, Nobuyuki. "Reproducibility and Usability of Chronic Virus Infection Model using Agent-based Simulation: Comparing with a Mathematical Model." *BioSystems* 99 (2010): 70-78.
- Jaroszewski, L., Rychlewski, L., Li, Z., Li, W., and Godzik, A. "FFAS03: A Server for Profile-Profile Sequence Alignments." *Nucleic Acids Research* 33 (2005): W284-88.
- Jonikas, Magdalena A., Radmer, Randall J., and Altman, Russ B. "Knowledge-based Instantiation of Full Atomic Detail Into Coarse-grain RNA 3D Structural Models." *Bioinformatics* 25 (2009): 3259-66.
- Kim, Saejoon. "Protein β -turn Prediction using Nearest-Neighbor Method." *Bioinformatics* 20 (2004): 40-44.
- Krivov, G.G., Shapovalov, M.V., and Dunbrack, R.L. "Improved Prediction of Protein Side-Chain Conformations with SCWRL4." *Protein* (2009).
- Kushwaha, Sandeep K., and Shakya, Madhvi. "Protein Interaction Network Analysis—Approach for Potential Drug Target Identification in *Mycobacterium tuberculosis*." *Journal of Theoretical Biology* 262 (2010): 284-94.
- Levenkova, Natasha., Gu, Qingjuan., and Rux, John. "Gene Specific siRNA Selector." *Bioinformatics* 20 (2004): 430-32.
- Lai, Xin., Nikolov, Svetoslav, Wolkenhauer, Olaf., and Vera, Julio. "A Multi-level Model Accounting for the Effects of JAK2-STAT5 Signal Modulation in Erythropoiesis." *Computational Biology and Chemistry* 33 (2009): 312-24.
- Lundstrom, J., Rychlewski, L., Bujnicki, J., and Elofsson, A. "Pcons: A Neural-Network-Based Consensus Predictor That Improves Fold Recognition." *Protein Science* 10 (2001): 2354-62.
- Massari, Serafina., Ciccarese, Salvatrice., and Antonacci, Rachele. "Structural and Comparative Analysis of the T Cell Receptor Gamma (TRG) Locus in *Oryctolagus cuniculus*." *Immunogenetics* 64 (2012): 773-79.
- Moult, John. "A Decade of CASP: Progress, Bottlenecks And Prognosis In Protein Structure Prediction." *Current Opinion in Structural Biology* 15 (2005): 285-89.
- Muller, Anthonie. "Thermosynthesis As Energy Source for the RNA World: A Model for the Bioenergetics of the Origin of Life." *BioSystems* 82 (2005): 93-102.
- Nasertorabi, Fariborz., Batisse, Claire., Diepholz, Meikel., Suck, Dietrich., Böttcher, Bettina. "Insights Into the Structure of the CCR4-NOT Complex by Electron Microscopy." *FEBS Letters* 585 (2011): 2182-86.
- Oh, Jung Hun., and Gao, Jean. "Fast Kernel Discriminant Analysis for Classification of Liver Cancer Mass Spectra." *IEEE/ACM Transactions on Computational Biology and Bioinformatics* 8 (2011): 1522-34.
- O'Neill, Luke A. "How Toll-like Receptors Signal: What We Know and What We Don't Know." *Current Opinion in Immunology* 18 (2006): 3-9.
- Ponferrada-Marín, M.I., Parrilla-Doblas, J.T., Roldán-Arjona, T., and Ariza, R.R. "A Discontinuous DNA Glycosylase Domain In A Family of Enzymes That Excise 5-

- Methylcytosine." *Nucleic Acids Research* 39 (2011): 1473-84.
- Piotrowski, Yvonne., Hansen, Guido., der Zanden, A.L., Snijder, Eric., Gorbalenya, Alexamder., and Hilgenfeld, Rolf. "Crystal Structures of the X-domains of a Group-1 and A Group-3 Coronavirus Reveal That ADP-ribose-binding May Not Be a Conserved Property." *Protein Science* 18 (2009): 6-16
- Ranzinger, René., Herget, Stephan., von der Lieth, Claus-Wilhelm., and Frank, Martin. "GlycomeDB—A Unified Database for Carbohydrate Structures." *Nucleic Acids Research* 39 (2011): D373-76.
- Roche, Daniel., Buenavista, Maria., Tetchner, Stuart., and McGuffin, Liam. "The IntFOLD Server: An Integrated Web Resource for Protein Fold Recognition, 3D Model Quality Assessment, Intrinsic Disorder Prediction, Domain Prediction and Ligand Binding Site Prediction." *Nucleic Acids Research* 39 (2011): W171-76.
- Sato, Tomohiro., Yuki, Hitomi., Takaya, Daisuke., Sasaki, Shunta., Tanaka, Akiko., and Honma, Teruki. "Application of Support Vector Machine to Three-Dimensional Shape-Based Virtual Screening using Comprehensive Three-Dimensional Molecular Shape Overlay with Known Inhibitors." *Journal of Chemical Information and Modeling* 52 (2012): 1015-26.
- Takeshita, Fumihiko, and Ishii, Ken. "Intracellular DNA Sensors in Immunity." *Current Opinion in Immunology* 20 (2008): 383-88.
- Teixeira, Cátia., Gomes, José., Couesnon, Thierry., and Gomes, Paula. "Molecular Docking and 3D-quantitative Structure Activity Relationship Analyses of Peptidyl Vinyl Sulfones: Plasmodium Falciparum Cysteine Proteases Inhibitors." *Journal of Computer-Aided Molecular Design* 25 (2011): 763-75.
- Vogel, Christine., Bashton, Matthew., Kerrison, Nicola., Chothia, Cyrus., and Teichmann, Sarah. "Structure, Function and Evolution of Multidomain Proteins." *Current Opinion in Structural Biology* 14 (2004): 208-16.
- Wang, Lipo., Chu, Feng., and Xie, Wei. "Accurate Cancer Classification using Expressions of Very Few Genes." *IEEE/ACM Transactions on Computational Biology and Bioinformatics* 4 (2007): 40-53.
- Wang, Xu., Lee, Hsiau-Wei., Liu, Yizhou., and Prestegard, James. "Structural NMR of Protein Oligomers using Hybrid Methods." *Journal of Structural Biology* 173 (2011): 515-29.
- Wang, Ying., Chen, Jiajia., Li, Qinghui., Wang, Haiyun., Liu, Ganqiang., Jing, Qing., and Shen, Bairong. "Identifying Novel Prostate Cancer Associated Pathways Based On Integrative Microarray Data Analysis." *Computational Biology and Chemistry* 35 (2011): 151-58.
- Wang, Z., Liu, J., Sudom, A., Ayres, M., Li, S., Wesche, H., Powers, J.P., and Walker, N.P. "Crystal Structures of IRAK-4 Kinase In Complex with Inhibitors: A Serine/Threonine Kinase with Tyrosine As A Gatekeeper." *Structure* 14 (2006): 1835-44.
- Wei, Chun Hua., Lee, Eung Suk., Jeon, Jeong Yi., Heo, Yong-Seok., Kim, Seung Jun., Jeon, Young Ho., Kim, Kyung Hyun., Hong, Hyo Jeong., and Ryu, Seong Eon. "Structural Mechanism of the Antigen Recognition by the L1 Cell Adhesion Molecule Antibody A10-A3." *FEBS Letters* 585 (2011): 153-58.
- Xu, Jianzhen., and Wong, Chiwai. "A Computational Screen for Mouse Signaling Pathways Targeted by microRNA Clusters." *RNA* 14 (2008): 1276-83.
- Zhang, Tongli., Brazhnik, Paul., and Tyson, John. "Computational Analysis of Dynamical Responses to the Intrinsic Pathway of Programmed Cell Death." *Biophysical Journal* 97 (2009): 415-34.
- Zhang, Yuan., Zheng, Nan., Hao, Pei., Cao, Ying., and Zhong, Yang. "A Molecular Docking Model of SARS-CoV S1 Protein in Complex with Its Receptor, Human ACE2." *Computational Biology and Chemistry* 29 (2005): 254-57.
- Zhou, Tong., Gu, Wanjun., Ma, Jianmin., Sun, Xiao., and Lu, Zuhong. "Analysis of Synonymous Codon Usage in H5N1 Virus and Other Influenza A Viruses." *BioSystems* 81 (2005): 77-86.